



Product data sheet

Indoor station BSH2012, Receiver

With the BSH2012 Audio which can intuitively be operated SKS sets an actual standard: Without any compromise this indoor station focuses with its design on the essential. The BSH2012 Audio sets a standard for all SKS basic models in the segment of indoor stations with receiver.

Features

- ✓ SKS BUS technology
- ✓ Indoor station with receiver, (the ergonomic receiver is held by a magnet; accepting calls by picking up the receiver)
- ✓ Key functions: Opening door, adjusting volume of calls and ringtones, muting (ringtone is reactivated automatically after 12 hours)
- ✓ potential-free switching functions possible (via switching actuator 300022 or BUS actuator module 300095, without additional wires)
- ✓ Optical call signalisation with LEDs
- ✓ Audio privacy function
- ✓ One-man installation and programming
- ✓ Optional parallel operation of up to 4 indoor stations
- ✓ 8 door call and 4 floor call ringtones
- ✓ Ringtone volume can be adjusted in 5 steps
- ✓ Operation via 6 concave touch keys (allow for an optimal operability at any age)
- ✓ Audio and video indoor stations can be combined within one structure
- ✓ Surface mounting

Versions

Item no.	Description	Color	Measurements (width x height x depth)
200027	BSH2012, Audio, receiver, 2-wire	white	89 x 230 x 23 mm

With ADO function

Item no.	Description	Color	Measurements (width x height x depth)
200029	BSH2012, Audio, receiver, 2-wire, with ADO function	white	89 x 230 x 23 mm

Technical data

Electric data

Voltage a+/b-	19 to 23 VDC
---------------	--------------

General

Temperature	-10°C to +45°C
Humidity	20 % to 90 %, non-condensing
Housing	Plastic
Measurements (width x height x depth)	89 x 230 x 23 mm
Protection type	IP20