



## Product data sheet

### Indoor station BSV2012, video

With the elegant BSV2012 Video SKS complete their product line with a high-quality basic model in the video segment, convincing in a wide variety of projects and situations.

#### Features

- ✓ SKS BUS technology
- ✓ Touch key functions: accept calls, open the door, muting ringtone (automatically reactivated after 12 hours)
- ✓ Additional functions via touch display: setting of ringtone volume, ringtone melodies, color, contrast and brightness
- ✓ Switching functions possible (without additional wires, via switching actuator 300022 or BUS actuator module 300095)
- ✓ 8,9 cm (3,5") TFT color display
- ✓ Automatic activation of the TFT display when a door call comes in
- ✓ Optical call signalisation via LEDs
- ✓ Audio and video privacy function
- ✓ One-man installation and programming
- ✓ Optionally parallel operation of up to 3 indoor stations
- ✓ Polyphone ringtones to choose from (differentiating between door and floor calls)
- ✓ 8 door call and 4 floor call ringtones
- ✓ Ringtone volume adjustable in 5 steps
- ✓ Menu language German or English
- ✓ Hands-free operation
- ✓ Enforcement function if loud ambient noise occurs during call
- ✓ Internal call function with up to 6 devices
- ✓ Surface-mounting

#### Versions

| Item no. | Description                        | Color | Dimensions (BxHxT) |
|----------|------------------------------------|-------|--------------------|
| 100069   | BSV2012, video, hands-free, 6-wire | white | 90 x 180 x 18 mm   |

#### Technical data

##### Electrical data

|                |             |
|----------------|-------------|
| Voltage supply | 20 - 28 VDC |
| Voltage a+/b-  | 19 - 23 VDC |

##### General data

|                                                         |                                                    |
|---------------------------------------------------------|----------------------------------------------------|
| Display 320 x 240 Pixel, 8,9 cm (3,5")                  | 320 x 240 Pixel, 8,9 cm (3,5")                     |
| Temperature -10°C to +45°C                              | -10°C to +45°C                                     |
| Humidity 20% to 90%, non-condensing                     | 20% to 90%, non-condensing                         |
| Housing Plastic housing                                 | Plastic housing                                    |
| Measurements (width x height x depth) 90 x 180 x 18 mm  | 90 x 180 x 18 mm                                   |
| Protection type IP20                                    | IP20                                               |
| Conformity with EU guidelines and low-voltage directive | EMV 2014/30/EU: EN55022 und EN55024, EG 2014/35/EU |