


SMARTLine 2-wire video set

sks

Benefit from our new set prices!



SMARTLine 2D BSV2012 video
Hands-free function 2-wire (Article no.: 100070)



90 x 180 x 17 mm
All dimensions given as: width x height x depth



Elegantly designed indoor station
(Material brushed stainless steel)



135 x 195 x 45 mm
All dimensions given as: width x height x depth

The BSV2012 video allows an optimal operability for all age groups. Below the display are three capacitive concave shaped buttons for call acceptance, door opening and call deactivation.

The functions such as the selection of a ringtone, its volume as well as contrast and brightness of the display are set via the menu of the user-friendly touch screen.

Outside a stainless steel front panel and a flush-mounted and galvanized box (depth 45 cm) are installed. This door station which is well-protected against vandalism, excels in LED lighting as well as 10 mm-name plates which can be opened at the front with a special tool only.

Technical data

- SKS BUS technology
- Hands-free communication
- key functions: call acceptance, door opening and switch off ringtone (call ist automatically switched back on after 12 hours)
- additional functions via touch display: switch function available (via the relay module in 2D compact power supply adaptor 300076 without additional wires), ringtone selection and its volume, as well as color, brightness and contrast of the display
- TFT color display is automatically switched on when door bell is ringing
- internal intercom function
- visual signal for call via LED
- video and audio privacy function
- one-man installation and programming
- optional parallel connection of up to 4 indoor stations
- in all 12 door calls and floor call melodies
- 10 settings for ringtone volumes
- different ring tones for house and floor calls
- surface mounted

SMARTLine 2-wire video set

sks

Benefit from our new set prices!



SMARTLine 2D BSV2012 video
Hands-free function 2-wire (Article no.: 100070)



Elegantly designed indoor station
(Material brushed stainless steel)

Incl. the following fittings:

Item no.	Name
300082	SMARTLine 2D camera/voice module for SKS set door station
300076	SMARTLine 2D video compact power supply adaptor

INFORMATION: For objects with more than one risers a 2-wire distributor box 4-way REG (item no. 300105) is needed. A maximum of 4 risers may be connected to this distribution. SMARTLine 2D distributor 2-way flush mounted (item no. 300104) is required for stubs. These components are not included in the set price.

Dimensions of stainless steel door stations:

Participants	Order no.	Piece number
1	SMARTLine 401011	
2	SMARTLine 401012	
3	SMARTLine 401013	
4	SMARTLine 401014	
5	SMARTLine 401015	
6	SMARTLine 401016	
8	SMARTLine 401017	
10	SMARTLine 401018	
12	SMARTLine 401019	

Further information please find here
www.sks-kinkel.de/en/indoor-call-stations/smartline

For further technical information
please contact your authorised dealer.

Dimensions of stainless steel door stations:

Push button	Front plate	In-wall flush-box
1	135 x 195 x 2 mm	115 x 175 x 45 mm
2	135 x 220 x 2 mm	115 x 200 x 45 mm
3	135 x 245 x 2 mm	115 x 225 x 45 mm
4	135 x 270 x 2 mm	115 x 250 x 45 mm
5	135 x 295 x 2 mm	115 x 275 x 45 mm
6	135 x 320 x 2 mm	115 x 300 x 45 mm
8	135 x 370 x 2 mm	115 x 350 x 45 mm
10	240 x 295 x 2 mm	220 x 275 x 45 mm
12	240 x 320 x 2 mm	220 x 300 x 45 mm

(w x h x d)

Your authorised dealer

Customer's signature

Other than that our general terms and conditions apply,
which can be downloaded under www.sks-kinkel.de.
We reserve the right to make any changes serving technical progress.
8008510 / 05.2018 / Printing errors excepted.